



Product Name : Directional control valve(M5)															
Item No. : V-3-M5, R-3-M5, L-3-M5, H-3-M5															
Description :	Product name: V-3-M5, R-3-M5, L-3-M5, H-3-M5 Port size: M5 Max. operating pressure: 0 ~ 7 kgf/cm ² Max. supply pressure: 8 kgf/cm ² ☆ 2(3)/2 Directional control valve.														
Features :	<table border="1"> <tr> <td>Port thread size</td> <td>M5</td> </tr> <tr> <td>Port amount</td> <td>2(3) port/2 position (2/2, 3/2)</td> </tr> <tr> <td>Used fluid</td> <td>Air</td> </tr> <tr> <td>Pressure range</td> <td>0 ~ 7 kgf/cm² (0 ~ 0.7 MPa)</td> </tr> <tr> <td>Maximum flow</td> <td>110 NL/min</td> </tr> <tr> <td>Ambient temperature</td> <td>0 ~ 60 °C</td> </tr> <tr> <td>Weight</td> <td>40 g</td> </tr> </table>	Port thread size	M5	Port amount	2(3) port/2 position (2/2, 3/2)	Used fluid	Air	Pressure range	0 ~ 7 kgf/cm ² (0 ~ 0.7 MPa)	Maximum flow	110 NL/min	Ambient temperature	0 ~ 60 °C	Weight	40 g
Port thread size	M5														
Port amount	2(3) port/2 position (2/2, 3/2)														
Used fluid	Air														
Pressure range	0 ~ 7 kgf/cm ² (0 ~ 0.7 MPa)														
Maximum flow	110 NL/min														
Ambient temperature	0 ~ 60 °C														
Weight	40 g														



Product Name : Directional control valve(G1/8)															
Item No. : V-3-1/8, R-3-1/8, L-3-1/8, H-3-1/8															
Description :	Product name: V-3-1/8, R-3-1/8, L-3-1/8, H-3-1/8 Port size: G1/8 Max. operating pressure: 0 ~ 7 kgf/cm ² Max. supply pressure: 8 kgf/cm ² ☆ 2(3)/2 Directional control valve.														
Features :	<table border="1"> <tr> <td>Port thread size</td> <td>G 1/8</td> </tr> <tr> <td>Port amount</td> <td>2(3) port/2 position (2/2, 3/2)</td> </tr> <tr> <td>Used fluid</td> <td>Air</td> </tr> <tr> <td>Pressure range</td> <td>0 ~ 7 kgf/cm² (0 ~ 0.7 MPa)</td> </tr> <tr> <td>Maximum flow</td> <td>NC: 300 NL/min, NO: 320 NL/min</td> </tr> <tr> <td>Ambient temperature</td> <td>0 ~ 60 °C</td> </tr> <tr> <td>Weight</td> <td>60 g</td> </tr> </table>	Port thread size	G 1/8	Port amount	2(3) port/2 position (2/2, 3/2)	Used fluid	Air	Pressure range	0 ~ 7 kgf/cm ² (0 ~ 0.7 MPa)	Maximum flow	NC: 300 NL/min, NO: 320 NL/min	Ambient temperature	0 ~ 60 °C	Weight	60 g
Port thread size	G 1/8														
Port amount	2(3) port/2 position (2/2, 3/2)														
Used fluid	Air														
Pressure range	0 ~ 7 kgf/cm ² (0 ~ 0.7 MPa)														
Maximum flow	NC: 300 NL/min, NO: 320 NL/min														
Ambient temperature	0 ~ 60 °C														
Weight	60 g														



Product Name : Directional control valve(G1/4)		
Item No. : V-3-1/4, R-3-1/4, L-3-1/4		
Description :	Product name: V-3-1/4, R-3-1/4, L-3-1/4 Port size: 1/4 Max. operating pressure: 0 ~ 7 kgf/cm ² Max. supply pressure: 8 kgf/cm ² ☆ 2(3)/2 Directional control valve.	
Features :	Port thread size	G 1/4
	Port amount	2(3) port / 2 position (2/2, 3/2)
	Used fluid	Air
	Pressure range	0 ~ 7 kgf/cm ² (0 ~ 0.7 MPa)
	Maximum flow	600 L/MIN
	Ambient temperature	0 ~ 60 °C
	Weight	280 g



Product Name : Directional control valve(G1/4)		
Item No. : V-4-1/4, R-4-1/4, L-4-1/4		
Description :	Product name: V-4-1/4, R-4-1/4, L-4-1/4 Port size: 1/4 Max. operating pressure: 0 ~ 7 kgf/cm ² Max. supply pressure: 8 kgf/cm ² ☆ 4/2 Directional control valve.	
Features :	Port thread size	G 1/4
	Port amount	4 port / 2 position (4/2)
	Used fluid	Air
	Pressure range	0 ~ 7 kgf/cm ² (0 ~ 0.7 MPa)
	Maximum flow	600 L/MIN
	Ambient temperature	0 ~ 60 °C
	Weight	460 g



Product Name :		Directional control valve(G1/8)
Item No. :		V-5-1/8-S, R-5-1/8, L-5-1/8
Description :		Product name: V-5-1/8-S, R-5-1/8, L-5-1/8 Port size: 1/8 Max. operating pressure: 0 ~ 7 kgf/cm ² Max. supply pressure: 8 kgf/cm ² ☆5/2 Directional control valve.
Features :	Port thread size	G 1/8
	Port amount	5 port / 2 position (5/2)
	Used fluid	Air
	Pressure range	0 ~ 7 kgf/cm ² (0 ~ 0.7 MPa)
	Effective section area	12 mm ²
	Ambient temperature	0 ~ 60 °C
	Weight	100 g



Product Name :		Directional control valve(G1/4)
Item No. :		V-5-1/4-S, R-5-1/4, L-5-1/4
Description :		Product name: V-5-1/4-S, R-5-1/4, L-5-1/4 Port size: 1/4 Max. operating pressure: 0 ~ 7 kgf/cm ² Max. supply pressure: 8 kgf/cm ² ☆5/2 Directional control valve.
Features :	Port thread size	G 1/4
	Port amount	5 port / 2 position (5/2)
	Used fluid	Air
	Pressure range	0 ~ 7 kgf/cm ² (0 ~ 0.7 MPa)
	Effective section area	18 mm ²
	Ambient temperature	0 ~ 60 °C
	Weight	180 g