



Product Name :	Head of the switch
Item No. :	H-S, P-F, P-M, P-L
Description :	Product name: H-S, P-F, P-M, P-L ☆The heads of the P-L and P-K type are made of plastic.



Product Name :	Directional control valve(M5)	
Item No. :	H-3-M5-S-2-22	
Description :	Product name: H-3-M5-S-2-22 Port size: M5 Max. operating pressure: 0 ~ 9.9 kgf/cm ² Max. supply pressure: 10 kgf/cm ² ☆2(3)/2 Directional control valve.	
Features :	Port thread size	M5
	Port amount	2(3) port/2 position (2/2, 3/2)
	Used fluid	Air
	Pressure range	0 ~ 9.9 kgf/cm ² (0 ~ 0.99 MPa)
	Maximum flow	110 NL/min
	Ambient temperature	0 ~ 60 °C
	Weight	180 g



Product Name :		Directional control valve(M5)	
Item No. :		P-3-M5-F-2-22	
Description :		Product name: P-3-M5-F-2-22 Port size: M5 Max. operating pressure: 0 ~ 9.9 kgf/cm ² Max. supply pressure: 10 kgf/cm ² ☆2(3)/2 Directional control valve.	
Features :	Port thread size	M5	
	Port amount	2(3) port/2 position (2/2, 3/2)	
	Used fluid	Air	
	Pressure range	0 ~ 9.9 kgf/cm ² (0 ~ 0.99 MPa)	
	Maximum flow	110 NL/min	
	Ambient temperature	0 ~ 60 °C	
	Weight	180 g	



Product Name :		Directional control valve(1/8)	
Item No. :		H-3-1/8-S-2-22	
Description :		Product name: H-3-1/8-S-2-22 Port size: G1/8 Max. operating pressure: 0 ~ 9.9 kgf/cm ² Max. supply pressure: 10 kgf/cm ² ☆2(3)/2 Directional control valve.	
Features :	Port thread size	G 1/8	
	Port amount	2(3) port/2 position (2/2, 3/2)	
	Used fluid	Air	
	Pressure range	0 ~ 9.9 kgf/cm ² (0 ~ 0.99 MPa)	
	Maximum flow	NC: 300 NL/min, NO: 320 NL/min	
	Ambient temperature	0 ~ 60 °C	
	Weight	180 g	



Product Name : Directional control valve(1/8)		
Item No. : P-3-1/8-F-2-22		
Description :	Product name: P-3-1/8-F-2-22 Port size: G1/8 Max. operating pressure: 0 ~ 9.9 kgf/cm ² Max. supply pressure: 10 kgf/cm ² ☆2(3)/2 Directional control valve.	
Features :	Port thread size	G 1/8
	Port amount	2(3) port/2 position (2/2, 3/2)
	Used fluid	Air
	Pressure range	0 ~ 9.9 kgf/cm ² (0 ~ 0.99 MPa)
	Maximum flow	NC: 300 NL/min, NO: 320 NL/min
	Ambient temperature	0 ~ 60 °C
	Weight	180 g



Product Name : Directional control valve(1/8)		
Item No. : H-5-1/8-S-2-22		
Description :	Product name: H-5-1/8-S-2-22 Port size: G1/8 Max. operating pressure: 1.5 ~ 8 kgf/cm ² Max. supply pressure: 10 kgf/cm ² ☆5/2 Directional control valve.	
Features :	Port thread size	G 1/8
	Port amount	5 port/2 position (5/2)
	Used fluid	Air
	Pressure range	1.5 ~ 8 kgf/cm ² (0.15 ~ 0.8 MPa)
	Effective section area	12 mm ²
	Ambient temperature	0 ~ 60 °C
	Weight	100 g



Product Name :		Directional control valve(1/8)	
Item No. :		P-5-1/8-F-2-22	
Description :		Product name: P-5-1/8-F-2-22 Port size: G1/8 Max. operating pressure: 1.5 ~ 8 kgf/cm ² Max. supply pressure: 10 kgf/cm ² ☆5/2 Directional control valve.	
Features :	Port thread size	G 1/8	
	Port amount	5 port/2 position (5/2)	
	Used fluid	Air	
	Pressure range	1.5 ~ 8 kgf/cm ² (0.15 ~ 0.8 MPa)	
	Effective section area	12 mm ²	
	Ambient temperature	0 ~ 60 °C	
	Weight	100 g	



Product Name :		Directional control valve(1/4)	
Item No. :		H-5-1/4-S-2-22	
Description :		Product name: H-5-1/4-S-2-22 Port size: G1/4 Max. operating pressure: 1.5 ~ 8 kgf/cm ² Max. supply pressure: 10 kgf/cm ² ☆5/2 Directional control valve.	
Features :	Port thread size	G 1/4	
	Port amount	5 port/2 position (5/2)	
	Used fluid	Air	
	Pressure range	1.5 ~ 8 kgf/cm ² (0.15 ~ 0.8 MPa)	
	Effective section area	18 mm ²	
	Ambient temperature	0 ~ 60 °C	
	Weight	300 g	



Product Name : Directional control valve(1/4)		
Item No. : P-5-1/4-F-2-22		
Description : Product name: P-5-1/4-F-2-22 Port size: G1/4 Max. operating pressure: 1.5 ~ 8 kgf/cm ² Max. supply pressure: 10 kgf/cm ² ☆5/2 Directional control valve.		
Features :	Port thread size	G 1/4
	Port amount	5 port/2 position (5/2)
	Used fluid	Air
	Pressure range	1.5 ~ 8 kgf/cm ² (0.15 ~ 0.8 MPa)
	Effective section area	18 mm ²
	Ambient temperature	0 ~ 60 °C
	Weight	300 g