

1620 : 2" threading machine



Capacity: Steel : RIGHT BSPT , LEFT BSPT , NPT Ø 1/4" - 2" RIGHT BSPP Ø 1/2" to 2" ISO Ø M 6 to M 42. **Stainless steel :** RIGHT BSPT Ø 1/2" to 2" NPT: Ø 1/4" to 2".

No-load spindle speed: 32 rpm (universal motor) 26 rpm (induction motor).

Supplied with: - Pipe cutter, - Self-opening die head, - Dual position reamer, - Tripod with lower tray, - Removable oil pan and shavings tray, - 5 litre container of cutting oil. With or without hooded safety pedal. Option: 4".

COMPOSITION	MOTOR	DIES	KG	REF
Ø " : 1/2 - 3/4, 1 - 2 Ø MM : 15/21 - 20/27, 26/34 - 50/60	INDUCTION 230 V	RIGHT BSPT	81,000	162050
Ø " : 1/2 - 3/4, 1 - 2 Ø MM : 15/21 - 20/27, 26/34 - 50/60HOODED SAFETY PEDAL	UNIVERSAL SINGLE-PHASE 230 V	RIGHT BSPT	80,000	162060
Ø " : 1/2 - 3/4, 1 - 2 Ø MM : 15/21 - 20/27, 26/34 - 50/60	UNIVERSAL SINGLE-PHASE 230 V	RIGHT BSPT	80,000	162062
Ø " : 1/2 - 3/4, 1 - 2 Ø MM : 15/21 - 20/27, 26/34 - 50/60HOODED SAFETY PEDAL	UNIVERSAL SINGLE-PHASE 230 V	NPT	80,000	162063
Ø " : 1/2 - 3/4, 1 - 2 Ø MM : 15/21 - 20/27, 26/34 - 50/60HOODED SAFETY PEDAL	UNIVERSAL PHASE 115 V	RIGHT BSPT	80,000	162070



1630 : Spare parts for 4" threading machine

TYPE	KG	REF
5 X 4" IRON PIPE CUTTING WHEELS	0,325	163006
5 X 4" STAINLESS STEEL PIPE CUTTING WHEELS	0,330	163007