

## 1101 - 1102 : Cutting oil



**New, improved blend.** Specially designed for manual and powered threading. With its very high lubricating ability, Virax cutting oil ensures better quality threads and lengthens the service life of both dies and machines. Water emulsifiable. Odourless.

**WARNING :** It is essential to rinse off the oil with detergent when used on drinking water circuits.

L	PACKAGING	KG	REF
1	CONTAINER	0,985	110101
5	CONTAINER	4,860	110105
1	BOX OF 12 CONTAINERS	12,430	110112
20	CONTAINER	19,600	110120
500 ML	SPRAY CAN	0,620	110200
500 ML	BOX OF 12 SPRAY CANS	6,900	110202

## 1105 : Stainless steel cutting oil



Specially designed for manual and powered threading. With its very high lubricating ability, Virax cutting oil ensures better quality threads and lengthens the service life of both dies and machines. Water emulsifiable.

**WARNING:** Must be rinsed with detergent when used on drinking water circuits.

L	PACKAGING	KG	REF
5	CONTAINER	4,600	110505
5	4 CONTAINERS	19,200	110506

## 1106 : Synthetic threading oil



### ADVANTAGES:

**Acceptable for fresh water:** All the oil is eliminated by rinsing it out.

**Odourless:** For a better user comfort.

**High technical performances:** Threading couple and tools durability are improved.

**In accordance with DVGW sanitary standard**(no.DW-0201AT2541): Acceptable for drinking water. Specially done to thread drinkable water pipings.

Use it without diluting.

L	PACKAGING	KG	REF
5	CANISTER	5,720	110605

## 3720 : Oil can



Pressed metal body. Duralumin spout. Metal pump. Recommended for applying cutting oil during threading operations.

CAPACITY L	KG	REF
0,300	0,170	372020