

**5260 : Propane pressure regulator adjustable 1,5 to 4 bar**



- Stepless pressure adjustment from 1.5 to 4 bar. - French version provided with couplings to NF EN 560. - 4 different national versions, one of them is in accordance with DIN 4811/1. - Supplied with a Ø 6 mm nipple coupling.

TYPE	CYLINDER COUPLING	MALE HOSE COUPLING	KG	REF
NF (FRANCE)	LEFT FEMALE 21,7 X 1,814	LEFT M 16 X 1,5	0,410	526000
A	LEFT FEMALE 21,7 X 1,814	LEFT 3/8"	0,395	526001
C	LEFT FEMALE 3/8"	LEFT 3/8"	0,465	526003
D (DIN)	LEFT FEMALE 21,7 X 1,814	LEFT 3/8"	0,545	526004
E	LEFT MALE 22,35 X 1,814 NGO	LEFT 3/8"	0,455	526005

**5260 : Fixed 2 bar propane pressure regulator**



- For soldering irons. - Supplied with a Ø 6 mm nipple coupling.

CYLINDER COUPLING	MALE HOSE COUPLING	FLOW RATE KG/H	KG	REF
LEFT FEMALE 21,7 X 1,814	LEFT M 16 X 1,5	8	0,350	526010

**5260 : Fixed 4 bar propane pressure regulator**



- For waterproofer's torches. - Supplied with a Ø 6 mm nipple coupling.

CYLINDER COUPLING	MALE HOSE COUPLING	FLOW RATE KG/H	KG	REF
LEFT FEMALE 21,7 X 1,814	LEFT M 16 X 1,5	15	0,350	526020

**5260 : Clip pro for Butagaz Propane pressure regulator**



- Can receive all Virax fixed and adjustable pressure regulators. - Specially designed to fit the new Butagaz® Propane "cubes".

COUPLING	KG	REF
LEFT 21,7 X 1,814	0,230	526050