

5250 : Waterproofer's torch - handle X 400



- General shut-off valve. Constant pilot light adjustment. - Heat and bitumen-resistant handle. - Threaded nipple for connecting straight or swivel couplings. - Rounded handle for a good, easy grip even without gloves. - Set of four interchangeable burners fitting onto single or double connecting tubes, and three flat burners. - All burners fitted with an adjustable stand. - Long trigger for easy operation with or without gloves.

**TIP :** - Use only with propane gas, - Operating pressure : 4 bar.

COMPOSITION	CONNECTION	KG	REF
STRAIGHT COUPLING, X 400 HANDLE	M 16 X 1,5	0,540	525000
X 400 HANDLE, CONNECTING TUBES 240 MM, JET BURNER 3 Ø 42 MM	M 16 X 1,5	1,080	525070
X 400 HANDLE, CONNECTING TUBES 240 MM, JET BURNER 4 Ø 52 MM	M 16 X 1,5	1,080	525072
FIXED 4 BAR PRESSURE REGULATOR, 10M STRAIGHT WATERPROOFING WELDER HOSE, X 400 HANDLE	M 16 X 1,5	2,130	525290
STRAIGHT COUPLING, X 400 HANDLE	LEFT 3/8"	0,540	525001
X 400 HANDLE, CONNECTING TUBES 240 MM, JET BURNER 3 Ø 42 MM	LEFT 3/8"	1,080	525071
X 400 HANDLE, CONNECTING TUBES 240 MM, JET BURNER 4 Ø 52 MM	LEFT 3/8"	1,020	525073

5250 : Burner for X 400 handle waterproofing torches



Circular burner.

DESCRIPTION	NOZZLE Ø INT. MM	FLOW RATE KG/H 4 BAR	ENERGY SUPPLIED KJ/H AT 4 BAR	FLAME Ø MM	FLAME L MM	KG	REF
JET 1	27	0,6	38600	30	180	0,200	525011
JET 2	37	2,1	98400	45	450	0,240	525012
JET 3	42	4,1	179500	60	600	0,270	525013
JET 4	52	7,9	347000	90	800	0,370	525014

5250 : Connecting tubes for jet burners 1-2-3-4 for X 400 handle waterproofing torches



L MM	DESCRIPTION	KG	REF
140	SINGLE 30	0,075	525020
240	SINGLE 31	0,140	525021
350	SINGLE 33	0,190	525022
660	SINGLE 34	0,280	525023
550	EXTENSION TUBE	0,340	525024
110	DUPLO 32	0,175	525025
660	DOUBLE 35	0,370	525026

5250 : Burner for X 400 handle waterproofing torches



Flat.

DESCRIPTION	NOZZLE Ø INT. MM	FLOW RATE KG/H 4 BAR	ENERGY SUPPLIED KJ/H AT 4 BAR	FLAME Ø MM	FLAME L MM	KG	REF
93	16 X 55	0,6	29000	30	80	0,250	525030
96	32 X 110	4,3	197100	90	200	0,660	525031
97	32 X 110	6	276300	90	400	0,880	525032