

**ADVANTAGES:**

LIGHTWEIGHT AND COMPACT.

INCREASED EFFICIENCY.

CAN BE USED AT VERY LOW TEMPERATURES (APPROX. -15°C).

GAS SUPPLY: 90 min.

APPROX. MIXTURE: 40% PROPANE AND 60% BUTANE.

IMMEDIATELY USABLE in any position, for soft and hard soldering (Ø 14 mm), bending and shrinking plastic, annealing pipes, loosening rusted nuts and unfreezing pipes.

Capacity : - soft soldering : Ø 54 mm. - hard soldering (40% -Ag) : Ø 14 mm.

DESCRIPTION	TYPE OF IGNITION	AUTONOMY	KG	REF
TORCH + CARDRIDGE	STANDARD	1H30	5,800	521550
TORCH ONLY	STANDARD	-	0,180	521552
TORCH + CARDRIDGE	PIEZO	1H30	0,610	521560
TORCH ONLY	PIEZO	-	0,190	521562

XB III display box

Counter display box containing 8 Standard or Piezo ignition XB III torches.

DESCRIPTION	TYPE OF IGNITION	AUTONOMY	KG	REF
8 X TORCH + CARDRIDGE	STANDARD	1H30	5,790	521555
8 X TORCH + CARDRIDGE	PIÉZO	1H30	5,700	521565